



Features

- Narrow band: concentrates transmission of clamping force, less weight, fast and simple installation, visible deformation provides evidence of proper closure
- Deburred edges over 360°: reduced risk of damage to parts being clamped, good clamping force

Material

- 304 Stainless Steel/Galvanized Iron

Item	Thickness		D mm	Range (Closed-Open)		Carton Quantity pcs
	Stainless Steel	Galvanized Iron		mm	inch	
TE7.0	0.5	0.7	6.0	5.0-7.0	.197-.276	5000
TE9.0	0.8	1.0	7.0	7.0-9.0	.276-.354	5000
TE13	0.8	1.0	7.0	11.0-13.0	.433-.512	5000
TE15	0.8	1.0	7.5	13.0-15.0	.512-.591	5000
TE17	0.8	1.2	8.0	13.8-17.0	.544-.669	5000
TE18	0.8	1.2	8.0	15.0-18.0	.591-.708	5000
TE20	1.0	1.2	8.5	17.0-20.0	.669-.787	5000
TE22	1.0	1.5	9.0	19.0-22.0	.748-.866	5000
TE23	1.0	1.5	9.0	20.0-23.0	.787-.905	5000
TE25	1.0	1.5	10.0	22.0-25.0	.866-.984	5000
TE27	1.0	1.5	10.0	23.0-27.0	.905-1.063	5000
TE28	1.0	1.5	10.0	25.0-28.0	.984-1.102	5000
TE31	1.0	1.5	10.0	27.0-31.0	1.063-1.220	5000